

TECHNICAL DATA SHEET

HARDENER U-2

APPLICATION:

- to reinforce the surfaces of fibrous materials such as mats, modules exposed to fast erosive flows of exhaust gases.
- to provide a coating on the surface of linings for heating units, flue gas ducts and hot gas extraction systems,
- to harden fibrous plates in order to increase the mechanical,
- to protect surfaces in contact with liquido protection of surfaces in contact with liquid non-ferrous metals

METHOD OF USE:

- the product is ready to use
- can be applied with a brush, by spraying with a gun or by spraying
- Once the soaking process is complete, the drying process can begin. Drying is possible under atmospheric conditions or by heating from a temperature of approx. 90°C until drying.

HARMFULNESS:

The product is safe to use. However, due to alkaline reaction, in case of contact of the preparation with eyes immediately rinse with plenty of water and seek medical help. The compound is non-flammable. Does not fuel the burn.

- STORAGE CONDITIONS
- o do not allow to freeze
- o store between 2°C and 37°C
- o expiry date: 1 year



* This card is confidential. Transmitting, copying and disclosing it to third parties requires the written consent of PRO-HURT. The card is addressed to the addressee(s) specified above and is the property of the addressee. Disclosure of the card is prohibited. If you are not the intended addressee, you must immediately remove this card and notify the sender by phone or email.